



# BERIC DAVIS COMPANIES INTERNATIONAL, LTD.

*Connecting Business Worldwide!*

## BERIC FORGED STEEL VALVE NUMBERING CHART

Valve Style		End Connection		Size		Class		Material		Trim	Options *	
501	BB Gate	B(SCH)	Butt Weld	1	¼	1	#150	A	A105N	01 (410)	A	316 Stn. Stl. Trim
502	BB Globe	F	Flanged	2	¾	3	#300	B	A350 LF2	02 (304)	B	B7M Bolting
503	BB Piston Check	G	Flat Face Flange	3	½	6	#600	C	A182 F5	03 (310)	C	Chain Operated
504	BB Swing Check	H	MNPT X FNPT	4	¾	8	#800	D	A182 F9	04	D	Extended Bonnet
505	WB Gate	J	MNPT X FSW	5	1	9	#1500	E	A182 F11	05 (410)	E	17-4 ph Stem
506	WB Globe	K	MSW X FNPT	6	1 ¼	0	#2500	F	A182 F22	06	F	Industrial Gas Cleaned
507	WB Piston Check	L	MSW X FSW	7	1 ½	A	#900	G	A182 F304/304L	07	G	Garlock EVSP Packing
508	WB Swing Check	R	RTJ	8	2	B	#1690	H	A182 F316/316L	08 (410)	H	Hastelloy C Stem
509	BB Y-Pattern Globe	S	Socket Weld			C	#2690	J	A182 F321	09	J	High Temp Packing & Gasket
510	BB Y-Pattern Check	T	NPT					K	A182 F52	10 (316)	K	Live Loaded
511	FP BB Gate	W	FNPT X SW					M	A182 F347	11	L	Lock Bonnet
512	WB Y-Pattern Globe	X	SW X FNPT					P	A182 F12	12 (316)	M	
513	WB Y-Pattern Check	Y	RMSW X FNPT					R	A182 F51	13	N	NACE
514	FP BB Swing Check	Z	RMSW X FSW					S	A182 F316H	14	O	Oxygen Cleaned
515	FP WB Gate							T	A182 F317/F317L	15 (304)	P	125rms Flat Faced Flng
516	FP WB Globe							4	MONEL 400	16 (316)	R	L7M Bolting
517	FP WB Piston Check									17 (347/FHF)	S	B8M Bolting
518	FP WB Swing Check									18	T	TFE Packing, 316/TFE Gasket
522	FP BB Globe									19 (F51)	U	316/TFE Gasket Only
523	FP BB Piston Check									26 (316H)/FHF	V	Vacuum Service
530	BB Ball Check									27 (317) HHF	W	Bellow Seal
531	FP BB Ball Check									32 (304) HHF	X	Nipple Extensions
532	WB Ball Check										Y	Cryogenic Service
533	FP WB Ball Check										Z	Mounting Plate
552	WB Y-Pattern Stop/Check										A2	HF Alkylation Service
561	Pressure Seal Gate											
562	Pressure Seal Globe											
563	Pressure Seal Piston Check											

\* More than one option may be used in combination.

Notes:

1. Not all options are available in combinations. Please consult the factory. Minimum quantities may apply to certain materials or trim configurations.
2. Beric trim number corresponds to the equivalent API 602 trim designation.